

TEKNOGLASS GEL COAT PRIMER

Catalog No: 5000-505

Teknoglass Gel Coat Primer is a one-pack, synthetic polymer base primer. It dries quick and is suitable for use on gel coats and glass-fiber reinforced polyesters. For a good adhesion, the surface doesn't need sanding; however, the surface should be clean of grease, oil and dust.

TECHNICAL CHARACTERISTICS

Solids by volume (%)	: 20
Density (mixture) (gr/cm³)	: 1,15 ~ 1,05
Color	: Pink
Finish	: Matt
Binder	: Synthetic polymer resin
Dry film thickness (μ)	: 15
Theoretical covering capacity (m²/lt)	: 13 (15μ)
Application temperature (°C)	: + 5 ~ + 35
Drying time (25 °C)	
beginning of drying (min)	: 5 ~ 10
full drying (hrs)	: 2 ~ 3
before use (hrs)	: 12
Thinner	: Thinning is not suitable for this product. Cleaning can be done by Teknomarin Polyurethane Boya Tineri (8001).
Application mode	: Spray gun, brush
Surface preparation	: <u>New gel coats</u> : the surface does not require any sanding. Degrease with a detergent and rinse with fresh water. If there are traces of mould separation wax, lightly wet sand the gel coat with 400 grade abrasive paper until the surfaces of the gel coat becomes fully matt. <u>Old gel coats</u> : The product should be applied directly on the stripped gel coat or on the epoxy primer.
Safety precautions	: Highly flammable. Risk of serious damage to eyes. May cause sensitisation by skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility. Possible risk of harm to the unborn child. Vapours may cause drowsiness and dizziness. Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves and eye/face protection. If swallowed, seek medical advice immediately and show this container or label.

FP.01.03.Rev 00