

TEKNOMARIN EPOXY GÜVERTE HARÇ **(Epoxy Deck Filler)**

Catalog No: 1200 – 154G

Teknomarin Epoxy Güverte Harç is a solventless, high strength, two-pack epoxy deck repairing and fairing filler. It excellently adheres to concrete, ceramic, steel, aluminum, wood, polyester and glass. Its impact, scratch and chemical resistance and adhesion properties are excellent. Besides, it can be used on damaged concrete surfaces, in repair jobs of stairs and building columns, machine load structures, repair shops and loading docks.

TECHNICAL CHARACTERISTICS

Solids by volume (%)	: 100
Density (mixture) (gr/cm³)	: 1,3 – 1,4
Color	: Component A = white, Component B = black
Finish	: Matt
Binder	: Epoxy resin
Heat resistance (°C)	: 150
Application temperature (°C)	: + 5 ~ + 35
Drying time (25 °C)	
beginning of drying (hrs)	: 1 ~ 2
drying (hrs)	: 3 ~ 4
Application mode	: Spatula
Surface preparation	: The surface must be clean, free from dust, grease and oil. There shouldn't be any instable parts on the surface. No priming is required.
Mixing ratio (by weight)	: 3 A / 1 B
Pot life of the mixture (min)(20 °C)	: 20-25
Safety precautions	: This product may have an irritating effect on eyes and skin. It may cause sensitization on the skin by contact. In the case of contact with eyes, rinse immediately with abundant water. Get urgent medical assistance when subjected. Keep it out of the reach of children. Necessary safety precautions must be taken during use, handling, transport and stocking. Application technicians must wear masks, gloves and goggles. Ensure sufficient aerating conditions when applying in closed areas. Do not inhale.