



Catalog No: 6000 - 115K

TEKNOMARIN KAYMAZ

Teknomarin Kaymaz is a one-pack, high quality, alloyed, polyurethane finish enamel. It has excellent dilatation and satisfactory color characteristics. It is suitable for outside and inside use on pleasure boats and in houses. This product is very flexible and adheres well to most of primers, undercoats and finishes. It is not directly applied to inorganic zinc primers or to galvanized panels. It is not suitable for continuous immersion. It is especially suitable to prevent sliding on deck. The special ingredient in the product which prevents sliding doesn't also cause injury to your feet if stepped barefoot. It also doesn't harm the swimsuits.

TECHNICAL CHARACTERISTICS

Drying time (20 °C)

Solids by volume (%) : 45 Density (gr/cm³) : 1,25

Color : White or other colors

Finish : Semi-matt

Binder : Synthetic resin

Dry film thickness (μ) : 50 (per coat)

Theoretical covering capacity (m²/lt) : $9 (50\mu) \sim 6.5 (70\mu)$

Application temperature (°C) : $+5 \sim +35$

beginning of drying (hrs) : $1 \sim 2$

full drying (hrs) : 4

Thinner: Max. 5 % Teknomarin Sentetik Boya Tineri (6001).

Application mode : Brush, roller

Surface preparation : This product is applied to primed surfaces or to surfaces with barrier coat. The surface must be free

from dirt, oil, grease and moisture.

Safety precautions

: May cause cancer. May cause heritable genetic damage. Flammable. Avoid exposure - obtain special instructions before use. Keep locked up and out of the reach of children. Do not breathe gas/ fumes/ vapour/ spray (appropriate wording to be specified by the manufacturer). Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. In case of insufficient ventilation, wear suitable respiratory equipment. In case of accident or if you feel unwell, seek medical



advice immediately (show the label where possible).